
## ARCADIS GERAGHTY&N





LA DEPT OF ENV QUALITY REMEDIATION SERVICES DIVISION LOG #44701

RECEIVED

MAY 2 1 2002

LA DEPARTMENT OF ENVIRONMENTAL QUALITY OFFICE OF ENVIRONMENTAL SERVICES ARCADIS G&M, Inc. 2900 West Fork Drive Sulte 540 Baton Rouge Louisiana 70827 Tel 225 292 1004 Fax 225 292 5210 www.arcadis-us.com

**ENVIRONMENT** 

Request for Site-Specific Treatability Variance for Acrylic Acid in Soils Eunice Train Derailment, May 27, 2000

Agency Interest No. 82576 85276

Mr. Michael Vince, Administrator

Baton Rouge, Louisiana 70884-2135

Louisiana Department of Environmental Quality

Office of Environmental Services, Permits Division

Dear Mr. Vince:

P.O. Box 82135

ARCADIS is submitting this petition for a site-specific variance from the treatability standard for acrylic acid for the soils at the Eunice, Louisiana site on behalf of the Union Pacific Railroad Company (UPRR). Specifically the petition is submitted in accordance with LAC 33:V.2231.G., the applicable sections of which are shown below.

- Based on a petition filed by a generator or treater of hazardous waste, the administrative authority may approve a site-specific variance from an applicable treatment standard if:
  - (Not Applicable); or
- 2. it is inappropriate to require the waste to be treated to the level specified in the treatment standard or by the method specified as the treatment standard, even though such treatment is technically possible. To show that this is the case, the petitioner must either demonstrate that:
- a. treatment to the specified level or by the specified method is technically inappropriate (e.g., resulting in combustion of large amounts of mildly contaminated environmental media where the treatment standard is not based on combustion of such media); or
  - b. (Not Applicable);
- 3. for contaminated soil only, treatment to the level or by the method specified in the soil treatment standard would result in concentrations of hazardous constituents that are below (i.e., lower than) the concentrations necessary to minimize short and long term threats to human health and the environment. Treatment variances approved under this Subsection must:
- a. at a minimum, impose alternative land disposal restriction treatment standards that, using a reasonable maximum exposure scenario:

20 May 2002

Contact:

George H. Cramer, II


Extension: 228

Email:

gcramer@arcadis-us.com

Our ref:

LA001993.0001.00002



ARCADIS

Mr. Michael Vince
20 May 2002

- i. (Not Applicable);
- ii. for constituents with noncarcinogenic effects, achieve constituent concentrations that an individual could be exposed to on a daily basis without appreciable risk of deleterious effect during a lifetime;
  - b. not consider post-land-disposal controls;

The information specifically requested in LAC 33.I.907.C. and the above specified sections of LAC 33:V.2231.G is provided below.

J. Petitioner's Name and Address (§ 907.C.1.)

Union Pacific Railroad 24125 Aldine Westfield Road Spring, Texas 77373-9015 Contact: Geoffrey Reeder

#### II. Petitioner's Interest in the Proposed Action (§ 907.C.2.)

UPRR is the generator of a large volume of impacted soil media from a train derailment site northwest of the town of Eunice, Louisiana. Approximately 1,500 tons of this soil has been mildly contaminated by acrylic acid (U008). UPRR has undertaken the clean up environmental media at the site impacted by the chemicals carried in the derailed railcars.

### III. Basis for the Requested Variance (§ 907.C.3.)

Acrylic acid in its pure form is a listed waste due to ignitability. The treatment standard for this compound is incineration. Based upon LAC 33:V.2231.G.2.a, UPRR believes that treatment of this impacted media by incineration is technically inappropriate, resulting in the incineration of a large volume of this soil (1,500 tons) solely because it is impacted by low levels of acrylic acid (the highest residual concentration detected to date is 240 milligrams per kilogram [mg/Kg]). This equates to less than one tenth of one percent by volume of the soil even if all the soil were impacted by this concentration. In addition, the acrylic acid at the site does not exhibit the same nature as the acrylic acid utilized in the determination of the hazardous waste characteristic of ignitability. The waste material polymerized during the release, becoming a solid material, and is no longer ignitable. Although occasional exposed pieces of the polymerized material have been found at or near the surface of the ground, in the 2 years since the derailment, no acrylic acid has ignited at the site. Additionally, soil with this concentration of acrylic acid was tested for ignitability as part of the waste characterization during the initial removal operation. The soil was determined not to be ignitable.

ARCADIS

Mr. Michael Vince
20 May 2002

#### IV. ...Proposed Regulations or Amendments... (§ 907.C.4.)

No regulations or amendments to regulations are anticipated due to this action.

## V. Other Information that Justifies the Proposed Action (§ 907.C.5.)

Treatment of the contaminated soil by incineration would result in concentrations of hazardous constituents (acrylic acid) that are below the concentrations necessary to minimize short and long term threats to human health and the environment. Acrylic acid exhibits non-carcinogenic effects. In accordance with LAC 33:V.2231.G.3.a.ii, ARCADIS has calculated concentration limits (attached), under Management Option – 1 (MO-1) that an individual could be exposed to on a daily basis without appreciable risk of deleterious effect during a lifetime. These MO-1 limits are based upon Screening Standard concentrations already calculated by ARCADIS, submitted in the Site Investigation Report for Eunice City Lake, and accepted by the LDEQ (also attached). The MO-1 standard (100 mg/Kg) is based on an industrial exposure scenario.

The acrylic acid that is in the soil does not readily leach from the soil. Synthetic Precipitate Leaching Procedure (SPLP) samples collected from the impacted areas of the right-of-way documented that the acrylic acid is not mobile. As shown in the Railbed Report (February 2002) the SPLP sample collected from the area of highest acrylic acid concentrations had an SPLP concentration of only 0.066 milligrams per liter (mg/L) which is three orders of magnitude below a concentration that is protective of groundwater. Therefore, landfilling of this soil will not create an environmental hazard due to the leaching of the acrylic acid.

Based upon the information provided above, UPRR proposes to dispose of soil containing concentrations of 100 mg/Kg or less of acrylic acid by direct landfilling at a Subtitle C (Hazardous Waste) landfill. Landfilling of acrylic acid contaminated soil, below the MO-1 industrial level, will remain protective of human health and the environment. UPRR proposes to dispose of the soil impacted by acrylic acid above the MO-1 concentration of 100 mg/Kg by incineration.

UPRR will comply with all applicable requirements for restricted wastes found under LAC 33:V.2245 and 2247.

Mr. Michael Vince 20 May 2002

#### Certification

Based upon a thorough review of the information pertinent to this petition, the engineer providing oversight of this project makes the following certification:

I certify under penalty of law that I have personally examined and am familiar with the information submitted in this petition and all attached documents and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the submitted information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fines and imprisonment.

Sincerely,

ARCADIS G&M, Inc.

David R. Escude' Principal Engineer

La. Registration No. 23071

DAVID R. ESCUDE REG. No. 23071

REGISTERED PROFESSIONAL ENGINEER

ENGINEERING.

sseciate Vice President/Hydrogeologist

Rudy J. Gylichard Vice President/Area Manager

DRE:GHC:RJG:ndw

Attachments

Copies

Geoffrey Reeder/Union Pacific David Young/Union Pacific Steven Levine/Phelps Dunbar Dr. James H Brent/LDEQ Mr. Douglas Bradford/LDEQ

Table 1. RECAP Limiting Industrial Soil MO-1 RECAP Standards (RS) for the Railbed Proper, Union Pacific Railroad Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

	Limiting MO-1 Industrial Soil <sub>RS</sub> (mg/kg)
VOCs	
1,2-Dichloropropane	0.042
Chloromethane	0.1
n-Hexane	110
SOVCs	
Acrylic Acid	100
Benz(a)anthracene	0.33*
Dicyclopentadiene	5.4
Disodium Iminodiacetate	150
Naphthalene	32
Phenoi	990
2,4-Toluenediamine	1.67*
Toluene Diisocyanate	0.66*
Inorganics	
Aluminum	74,000

The limiting industrial Soil<sub>RS</sub> was based on the lowest of the Soil, the Soil<sub>GW3NDW</sub>, and the Soil<sub>sai</sub>.

Soil, Soil MO-1 RECAP standard based on the protection of human health for industrial land

use; from RECAP Table 2 when available (applicable to railbed proper); modifications

to account for additive effects are shown in parentheses.

Soil<sub>GW3NDW</sub> Soil MO-1 RECAP standard for soil concentration protective of groundwater

classification 3; from RECAP Table 2 when available; a dilution factor (DF) was conservatively not applied due to the proximity of the tributary to the Railbed.

Soil saturation concentration (from RECAP Table 2 when available).

mg/kg milligrams per kilogram.

\* If the calculated RS was less than the sample quantitation limit (SQL), the SQL was

used as the RS.

RECAP Screening Standards for Union Pacific Railroad Train Derailment

Eunice Train Derailment 52700 - May 27, 2000 Agency Interest No. 85276

PREPARED FOR

Union Pacific Railroad Company

Carol E. Mueller, M.S.P.H. Scientist/Toxicologist

Lance W. Fontenot, Ph.D. Senior Scientist/Toxicologist

Rudy J. Guichard Vice President/Area Manager RECAP Screening Standards for Union Pacific Railroad Train Derailment

Eunice Train Derailment 52700 - May 27, 2000 Agency Interest No. 85276

Prepared for:
Union Pacific Railroad Company

Prepared by:
ARCADIS Geraghty & Miller, Inc.
2900 West Fork Drive
Suite 540
Baton Rouge
Louisiana 70827
Tel 225 292 1004
Fax 225 292 5210

Our Ref. LA001993.0001.00002

Date 20 April 2001

This document is intended only for the use of the individual or entity for which it was prepared and may contain information that is privileged, confidential, and exempt from disclosure under applicable law. Any dissemination, distribution, or copying of this document is strictly prohibited.

**ARCADIS Table of Contents** Introduction 1 1.0 2.0 **Methods** 3.0 Results 4.0 References б **Tables** Physical and Chemical Properties for Constituents of Concern. Oral Reference Doses, Inhalation Reference Concentrations, Target Sites, and Confidence Levels for Constituents of Concern. Oral Cancer Slope Factors, Inhalation Cancer Slope Factors, Tumor Sites, and USEPA Cancer Classifications for Constituents of Concern. Preliminary Calculation of RECAP Screening Standards for Soil. Equations for Preliminary RECAP Screening Standards for Soil and Sample 5 Calculations for Soil. Preliminary Calculation of RECAP Screening Standards for Groundwater. 6 7 Equations for Preliminary RECAP Screening Standards for Groundwater and Sample Calculations for Groundwater. Preliminary Calculation of RECAP Standards for Surface Water. 8 **Equations for Preliminary RECAP Standards for Surface Water and Sample** 9 Calculations for Surface Water. Preliminary Calculation of Risk-Based Concentrations for Edible Fish. 10 Equations for Preliminary Risk-Based Concentrations for Edible Fish and Sample 11 Calculations for Risk-Based Concentrations for Edible Fish.

i

RECAP Screening Standards For Union Pacific Railroad Train Derailment

Eunice Train Derailment 52700 - May 27, 2000 Agency Interest No. 85276

#### 1.0 Introduction

The objective of this report is to present risk-based screening standards using the equations provided in the Louisiana Department of Environmental Quality Risk Evaluation/Corrective Action Program (RECAP; LDEQ 2000; LAC 33:I.Chapter 13). RECAP Screening Standards (SS) will be used to: (1) evaluate preliminary sample quantitation limits (SQL); (2) establish an Area of Investigation (AOI) and constituents of concern (COCs) in accordance with RECAP Site Investigation requirements; and (3) provide an approach for deriving site specific RECAP Standards (RS) for the COCs after the Site Investigation activities are completed. The approach for defining AOI for the Eunice Train Derailment site is contained in the "Revised Work Plan, Environmental Site Investigation (ARCADIS Geraghty & Miller July 12, 2000) which was approved by LDEQ on July 25, 2000.

This report is concerned with the "short-list" of derailment-related COCs. The "short-list" of COCs includes the chemicals contained in the breached rail cars or surrogate chemicals identified as indicators of the presence of a chemical contained in the breached rail cars. A toxicity assessment for the COCs was conducted in order to identify appropriate toxicity values for use in calculating risk-based concentrations in soil, surface water, and edible fish tissue. To support the toxicity assessment, toxicological and environmental fate data were compiled from a technical literature review for the COCs.

Risk-based SS for non-industrial soil (Soil<sub>SSni</sub>, Soil<sub>SSGW</sub>, and Soil<sub>snt</sub>), groundwater (GW<sub>SS</sub>), surface water (SW<sub>NDW</sub>), and edible fish tissue (Risk-Based Concentration [RBC]) were calculated. The soil SS were calculated from equations taken directly from Appendix H and I of RECAP (LDEQ 2000). The soil SS presented herein are based on the assumption that the area of impacted soil under investigation is approximately 0.5 acre or less. If after completion of the Site Investigation the area of impacted soil is determined to be greater than 0.5 acre, the soil SS will require modification to the actual area of impacted soil.

The groundwater SS were calculated from equations taken directly from Appendix H of RECAP (LDEQ 2000). The surface water standard utilized the RECAP Management Option 1 (MO-1) equations for Groundwater Classification 3 Non-Drinking Water (GW3<sub>NDW</sub>) because the point of exposure for a GW3NDW groundwater source is assumed to be at the point of discharge to a surface water body. Therefore, the GW3<sub>NDW</sub> is assumed to be representative of a surface water RECAP

\

Д

UnionPac/N/5/rds

1

RECAP Screening Standards For Union Pacific Railroad Train Derailment

Eunice Train Derailment 52700 - May 27, 2000 Agency Interest No. 85276

2

Standard and is also consistent with Human Health Numerical Criteria Derivations for Toxic Substances (LDEQ 1994). The RBC for edible fish tissue is based on the equation presented in the U.S. Environmental Protection Agency (USEPA) Region III Report on the development of risk-based concentrations (USEPA Region III Risk-Based Concentration Table: Technical Background Information, 1999).

The following RECAP Standards were calculated:

Soil <sub>ssm</sub>	The RECAP soil screening standard based on the protection of
	human health for non-industrial land use.
Soilssow	The RECAP soil screening standard based on the protection of
	groundwater meeting the definition of Groundwater
	Classification 1 (compliance with GW <sub>SS</sub> ).
Soil <sub>sat</sub>	The MO-1 RECAP Standard based on the concentration that
	represents a chemical-physical limit where saturation of the soil
	occurs. Constituent concentrations in soil at or above the Soilset
	indicate a potential for non-aqueous phase liquid (NAPL) to be
<u>.                                    </u>	present in the soil.
GW <sub>ss</sub>	The RECAP groundwater screening standard based on the
1	protection of groundwater meeting the definition of
	Groundwater Classification 1.
SW <sub>NDW</sub>	The modified surface water RECAP Standard utilizing the
	GW3NDW equations that assumes a point of discharge into a surface water body.
RBC	Calculated risk-based concentrations for edible fish.
1	

#### 2.0 Methods

While RECAP provides screening standards for chloromethane, phenol, and 1,2-dichloropropane, no standards are available for other "short-list" COCs. Therefore, RECAP SS for such constituents were calculated using the equations provided in RECAP Appendix H and I (LDEQ 2000). The first step in preparation for doing such calculations was to compile physical and chemical information (Table 1), as well as toxicological information (Tables 2 and 3) on these constituents. Such data were obtained primarily from RECAP, USEPA Region III and Region IX documents.

Occasionally, the information needed for a specific chemical was not available. When chemical-specific dermal absorption factors (ABS) were not available, organic constituents were assumed to have an ABS of 0.1 and inorganic constituents an ABS of

UnionPat/II/Shdi

RECAP Screening Standards For Union Pacific Railroad Train Derailment

Eunice Train Derailment 52700 - May 27, 2000 Agency Interest No. 85276

0.01, as taken from Appendix H, Table H-1 of RECAP (LDEQ 2000). Henry's Law constants were calculated with the following equation when not available: H = (vapor pressure \* molecular weight)/solubility. The equation is based on the Henry's Law Constant formula in USEPA's "Soil Screening Guidance: Technical Background Document" (USEPA 1999). The air diffusivities (D<sub>i</sub>) and water diffusivities (D<sub>w</sub>) were calculated following the formulas provided in Appendix H of RECAP. D<sub>i</sub> and D<sub>w</sub> were estimated using the algorithms below:

chemical a = chemical in question

chemical b = phenol (with published diffusivity value)

$$D_{i} = \frac{D_{ib}}{D_{ia}} = \sqrt{\frac{MW_{a}}{MW_{b}}}$$

$$D_{w} = \frac{D_{wb}}{D_{wa}} = \sqrt{\frac{MW_{a}}{MW_{b}}}$$

 $K_{oc}$  represents the organic carbon/ water partition coefficient, and  $K_{ow}$  represents the octanol/water partition coefficient. If a  $K_{oc}$  or  $K_{ow}$  was not available in the literature, a representative value was estimated using the algorithm from Appendix 1 of RECAP (LDEQ 2000).

$$Log K_{oc} = 0.0784 + (0.7919 \times log K_{ow})$$

When necessary, a bioconcentration factor (BCF) was estimated using the K<sub>ow</sub> and the algorithm from Appendix I of RECAP (LDEQ 2000).

$$Log BCF = 0.76 log K_{ow} - 0.23$$

Toxicity values were also located for the constituents involved. As reported in RECAP (LDEQ 2000), toxicity values are obtained from the following hierarchy of sources: (1) USEPA's Integrated Risk Information System (IRIS), an on-line database of toxicity information updated monthly (USEPA 2000); (2) USEPA's Health Effects Assessment Summary Tables toxicological profiles (HEAST; (USEPA 1997); (3) USEPA Region III Risk-Based Concentration Tables (USEPA 1998a); or (4) USEPA Region IX Preliminary Remediation Goals Tables (USEPA 1998b). Additional

RECAP Screening
Standards For Union
Pacific Railroad Train
Derailment

Eunice Train Derailment 52700 - May 27, 2000 Agency Interest No. 85276

sources are presented in the References section (Section 4). Occasionally, the available toxicological information needed to be converted to a form required by RECAP Standard equations. The inhalation reference dose (RfD<sub>1</sub>) can be calculated by converting a reference concentration (RfC) for noncarcinogenic effects using the following equation found in USEPA Region 1X's 1999 Preliminary Remediation Goals Report (Oct. 1, 1999).

$$RfD_{t} \frac{mg}{(kg-day)} = RfC(mg/m^{3}) \times \frac{20m^{3}}{day} \times \frac{1}{70kg}$$

A similar equation was used to convert the unit risk factors (URF) for carcinogenic effects to the inhalation cancer slope factor (CSF<sub>i</sub>) using the following equation found in USEPA Region IX's 1999 Preliminary Remediation Goals Report (Oct. 1, 1999).

$$CSF_{i}\frac{(kg-day)}{(mg)} = URF(m^{3}/ug) \times \frac{day}{20m^{3}} \times 70kg \times \frac{10^{3}ug}{mg}$$

### 3.0 Results

Available RECAP Standards for surface soil were utilized for the constituents that have such standards. As previously mentioned, some of the constituents do not have RECAP Standards. The soil SS for non-industrial land use (Soil<sub>SSni</sub>), the soil SS for protection of groundwater (Soil<sub>SSGW</sub>), and the soil SS for soil saturation concentration (Soil<sub>ssi</sub>) provide conservative risk-based SS for defining the AOI. The definition of AOI is critical for future applications of RECAP for corrective action options at the site. Table 4 shows the available or calculated soil standards for the COCs. Also, sample calculations for three constituents, acrylic acid, dicyclopentadiene, and 2,4-toluenediamine, are provided in Table 5.

In addition, RECAP Standards are not available for sediments. Therefore, it is proposed that using the soil SS for sediments will be protective of human health. Although surface soils found in the tributary area and adjacent wetlands at the site are saturated during certain portions of the year, the soil screening standard (SS) for non-industrial land use (Soil<sub>SSm</sub>) and the soil SS for protection of groundwater (Soil<sub>SSGW</sub>), provide conservative risk-based SS for defining the Area of Investigation (AOI).

•

Д

## RECAP Screening Standards For Union Pacific Railroad Train Derailment

Eunice Train Derailment 52700 - May 27, 2000 Agency Interest No. 85276

Available RECAP Standards for groundwater were utilized for the constituents that have such standards. As previously mentioned, some of the constituents do not have RECAP Standards. The groundwater screening standard (GW<sub>SS</sub>) is based on the protection of groundwater meeting the definition of Groundwater Classification 1. In accordance with RECAP, the Maximum Contaminant Level (MCL; Safe Drinking Water Act) was identified as the GW<sub>SS</sub> when available. If an MCL was not available, a risk-based GW<sub>SS</sub> was developed using the equations provided in RECAP Appendix H (LDEQ 2000). The exposure pathways that were considered in the development of the risk-based GW<sub>SS</sub> include the ingestion of groundwater and the inhalation of volatile emissions associated with indoor groundwater use. Table 6 shows the calculated GW<sub>SS</sub> and sample calculations for three constituents (acrylic acid, dicyclopentadiene, and 2,4-toluenediamine) provided in Table 7.

RECAP Standards for surface water are not available. The equations for GW3NDW were used to develop a risk-based surface water standard. Because the point of exposure for GW3NDW groundwater is assumed to be at the point of discharge to a surface water body, it is assumed to be representative of a surface water RS. The GW3NDW equations are also consistent with LDEQ Human Health Numerical Criteria Derivations for Toxic Substances (LDEQ Office of Water Resources 1994). In Table 8 the calculated GW3NDW RS for surface water is referred to as Surface Water Non-Drinking Water (SWNDW). Table 9 provides sample calculations of the SWNDW standard.

RECAP Standards are also not available for fish. Therefore, to evaluate the constituent concentrations in fish collected from surface waters near the derailment area, a risk-based concentration was calculated. The RBC for edible fish tissue is based on the equation in USEPA's Region III Report on the development of risk-based concentrations (USEPA Region III Risk-Based Concentration Table: Technical Background Information, 1999). The USEPA Region III exposure assumption for fish ingestion (0.054 kg/d) was adjusted to match the RECAP input for fish ingestion (0.02 kg/d). Table 10 shows the calculated RBCs for edible fish tissue, as well as any USEPA Region III RBCs available for comparison. Sample calculations for RBCs are provided in Table 11.

If any of the calculated RECAP Standards are less than the analytical quantitation limit, the analytical reporting limit is used as the limiting Screening Standard for that specific medium (e.g., soil, groundwater, surface water, fish tissue) (LDEQ 2000). The Reporting Limits utilized are in accordance with established standard EPA approved methodologies. Reporting Limits are generally determined through application of a

\

A

RECAP Screening Standards For Union Pacific Railroad Train Derailment

Eunice Train Derailment 52700 - May 27, 2000 Agency Interest No. 85276

multiplication factor to the statistically derived Method Detection Limit (MDL) for an individual compound. MDLs are established in accordance with protocols set forth in 40 CFR Part 136. For reporting purposes associated with this project, if a detection occurs between the MDL and the reporting limit, values will be reported with a "J" qualifier indicating that the concentration is estimated. Therefore, if a non-detect is reported, the presumption is that the compound was not reportable above the MDL. With the exception of 2,4-toluenediamine and toluene diisocyanate, all fish tissue RBCs were greater than the laboratory analytical detection limits.

#### 4.0 References

- Baes, C.F., III, R.D. Sharp, A.L. Sjoreen, and R.W. Shor, 1984. A Review and Analysis of Parameters for Assessing Transport of Environmentally Released Radionuclides through Agriculture. Prepared by the U.S. Department of Energy. ORNL-5786. September.
- California EPA (CalEPA). 1994. Office of Environmental Health Hazard Assessment. Criteria for Carcinogens. November 1994.
- Chemfinder. 2000. CambridgeSoft Corporation. www.chemfinder.com
- Howard, P.H., 1989. Handbook of Environmental Fate and Exposure Data for Organic Chemicals, Volume I, Large Production and Priority Contaminants. Lewis Publishers, Inc., Chelsea, MI. 574 pp.
- Louisiana Department of Environmental Quality (LDEQ). 2000. Louisiana
  Department of Environmental Quality Risk Evaluation/Corrective Action
  Program. June 20, 2000; LAC 33:I.Chapter 13.
- LDEQ. 1994. Human Health Numerical Criteria Derivations for Toxic Substances. Louisiana Surface Water Quality Standards. June 23,1994; LAC 33:IX.11.
- National Institute of Environmental Health Sciences. 2000. 111 Alexander Drive, Research Triangle Park, NC.
- National Institute for Occupational Safety and Health. 2000. International Chemical Safety Cards.

1

Д

6

RECAP Screening Standards For Union Pacific Railroad Train Derailment

Eunice Train Derailment 52700 - May 27, 2000 Agency Interest No. 85276

- Office of Environmental Health Hazard Assessment. 1999. California Environmental Protection Agency. Air Toxics Hot Spots Program Risk Assessment Guidelines, Part III, Draft Technical Support Document for the Determination of Noncancer Chronic Reference Exposure Levels. May and September, 1999.
- Shen, T.J., 1982. Air Quality Assurance for Land Disposal of Industrial Waste. Environ. Mgmt., 6:297-305.
- Syracuse Research Corporation (SRC). 2000. Environmental Fate Data Base.
- U.S. Department of Health and Human Services. 2000. Agency for Toxic Substances and Disease Registry Toxicological Profiles.
- USEPA. 1996. Soil Screening Guidance: Technical Background Document. EPA/540/R-96/018. Office of Emergency and Remedial Response, Washington, D.C. NTIS PB96-963505.
- USEPA. 1997. Health Effects Assessment Summary Tables, FY-1997 Update. Office of Research and Development and Office of Emergency and Remedial Response, Washington, D.C. April. EPA 630/R-95/002F.
- USEPA. 1999a. EPA Region III Risk-Based Concentration Table: Technical Background Information. April 12, 1999.
- USEPA. 1999b. USEPA Region IX Preliminary Remediation Goals (PRGs) Tables. October 1, 1999.
- USEPA. 1999c. USEPA Region VI Human Health Medium-Specific Screening Levels. July 14, 1999.
- USEPA. 2000. Integrated Risk Information Systems (IRIS). Office of Health and Environmental Assessment, Cincinnati, OH.
- USEPA. 2000. Toxic Release Inventory.
- U.S. National Library of Medicine. TOXNET and HSDB. 8600 Rockville Pike, Bethesda, MD. 2000.

F

Д

Physical and Chemical Properties for Constituents of Concern, Union Pacific Deraitment Site, Union Pacific Railroad Company, Eurice, Louisiana Table I

Consument	Moleculæ Weight (g/mol)		Water Solubility (mg/L)		Henry's Law Constant (atm-m³/mol)		Henry's Law Constant (unitless)	Diffusivity in Air (cm²/sec)		Diffusivity in water (cm²/sec)		Koc (mL/g)		BCF (L/g)	
Aerylic Acid	72 06	م	1 00E+06	د ا	3 205-07	٥	1315-05	9 37E-02	3	1 04E-05	ਰ	54	٥	-	۰
Aluminum	26 98	U	0	v	¥		¥.	1.536-01	3	1 70E-05	Ca	1500	٠.,	1 05	큥
Caprolactum	113 16	u	\$ 25E+06	u	5.40E-11	υ	2 21E-09	7 48E-02	3	8 30E-06	펺	57	υ	32	v
Chloromethane	50 49	•	5.30E+03	=	8 80E-03	æ	3.61E-01	1 26E-01	rd	6 50E-06	rş	25 1	rd	2 89	æ
Cyanide •	52	د	1 00E+06	o	1,335-04	υ	5.45E-03	1 565-01	75	1 73E-05	펺	<b>~</b>	-	_	ro
1.2-Dichloropropane	112 99	æ	2 80E+03	42	2 80E-03	æ	1 15E-01	7.82E-02	rs	8.73E-06	æ	47	rei	19.5	•
Dicyclopentadiene	132 21	u	0	20	1 075-02	U	4 39E-01	6 92E-02	큥	7 68E-06	3	894	v	93.2	v
Disodum Ininodiacetate	177 07	14	¥	,	Ϋ́Z		۲×	S 98E-02	ਰ	6 61E-06	평	۲Z		Š	
Ethylene Glycol	62 07	<u>.</u> =	1 00E+05	20	6 00E-08	u	2 46E-06	1 01E-01	큥	1 12E-05	Œ	0	J	2	v
n-Heyane	86 18	7	9 8	U	1 81E+00	U	7 42E+0	8.57E-02	85	7 18E-06	85	1250 - 4100	u	035.046	v
Neopenty I Glycol	104 15	-8	1 86E+06	-	¥Z		ž	7 79E-02	평	8 65E-06	腐	₹ Z		ž	
Pentane	72 15		3 85E+01	u	1 26E+00	J	\$ 17E+01	9 37E-02	흥	1 04E-05	Ę	1600	U	0 28 - 0 37	U
Phenol	=	73	8 28E+04	æ	3 97E-07	æ	1 63E-05	8 20E-02	æ	9 10E-06	75	288	٦	<u>e</u>	rs
2.4-Toluenediamine	122 17	u	7 74E+03	U	1 20E-09	U	4 92E-08	7 20E-02	8	7 99E-06	7	- 56	u	2	u
Toluene Disacyanate	174 16	ن	3 76E+01	0	1 11E-05	U	4.55E-04	6 03E-02	8	6 69E-06	15	1096 75	6/23	910	<b>E</b> 5/3

Note	The unitless Henry's Law Constant is calculated (1/RT) x the value in atm-m'/mol	am-m²/mol	
•	Values reported for cyande water solubility. Henry's Law constant, and Koc are for hydrogen cyande, cyande information was not available	d Koc are for hydrogen	i cyanide, cyande information was not available
References	IRIS, 2000; NLM, 2000, LDEQ RECAP 2000, USEPA Region IX, 1999, or were calculated in accordance with LDEQ or EPA	99, or were calculated a	n accordance with LDEQ or EPA
rg	RECAP, LDEQ 2000	atm-m³/mol	atm-m³/mol Atmospheres-cubic meters per mole
م	IRIS, 2000	cm³/sec	Square centimeters per second
U	National Library of Medicine, HSDB 2000.	jour/a	Grams per mole
70	ATSDR for andividual constituent	<b>K</b> 88	Organic carbon partition coefficient
υ	SRC Physical Properties Database	Age.	Milligrams per later
_	Bacs, et al., 1984	Į.	Millihters per gratn
:-0	Chemfinder, 2000	YZ	Not available
_	EPA DAQPS, UATW	RT	Ideal gas constant x absolute temperature (0 02445 atm-m <sup>3</sup> /mol)
	WHO/IPCS/ILO		
-	USEPA Region 9 PRG Tables		
E	Calculated using formula from RECAP, LDEQ 2000		

Oral Reference Doses, Imbalation Reference Concentrations, Target Sites, and Confidence Levels for Constituents of Concern, Union Pacific Derailment Site, Union Pacific Railroad Company, Euroce, Louisians. Table 2

į

	<u>e</u> 9		Inhalation RED		RG		Targe	Target Sites	Confider	Confidence Level/ Uncertamly Factor
Constituent	(mg/kg/day)	•	mg/kg/day)		(mg/m³)		Oral	Inhalation	Oral	Inhalation
Acrylic Acid	90	م	0.00029	~	0.001	~	cellular necrosis	nose	high/100	medium/30
Aluminum	1.0	7	0 0014	Ð	0.00	•	bone, CNS	gunj	N.	ĄN N
Caprolactam	0 \$	م	0.5	φ.	٧Z		reproductive	respiratory	high/100	AN
Chloromethane	980'0	-	980.0	•	Ϋ́Z		당	CNS, liver, kidney, skin	AN A	K'Z
Cyanide, Total*	0.05		0 02	=	N A		Iner	NA	тефпит/100	ΑN
1,2-Dichloropropane	0 00114	-	0.00114	73	0.004	م.	blood, liver, kidaey	liver, kidney	ΝĄΝ	med rum/30
Dicyclopentadiene	0.03	2	0.000057	4	0 00020	<b>.</b> =	CNS, respiratory	CNS, cardsovascular	ž	K K
Disodium Immodiacetate	Y.		ž		Ϋ́		NA	42	ξX	Ą Z
Ethylene Glycol	2.0	٩	0.7	P	4.0	٠.	CNS, cardiovascular	٧×	high/100	ď Z
n-Hexane	90.0	£	0.0571	79	0.2	م.	15	CNS, polyneuropathy	Š	med:um/30
Neopentyl Glycol	ž		¥		N N		NA	ΝΆ	Ş	N A
Pentane	Ž		¥ X		Ϋ́		gunq	CNS, cardiovascular	ď Z	Ą.
Phenol	90	-	90	10	NA		liver, kudney	skin, eyer, nausi	low/100	Ą
2,4-Toluenediamine	Z'A		Š		NA		NA	NA	ĄZ	ď
Tohens Dusocyanate	0 23	v	0 00002	ca	0 00007	م	liver, kidney, GI	respiratory, akin	¥.	medium/3(

Office of Environmental Health Hazard Assessment. 1999. California Environmental Protection Agency. Air Toxica Hot Spots Program Rusk Assessment Geodelines, Part III, Draft Technical Support Document for the Determination of Noncancer Chronic USEPA Region IX Preliminary Remediation Goals Tables, 1999. USEPA, Office of Pollution Prevention and Toxics. TRI Risk-Sereening Environmental Indicators. September 1998. As a conservative measure, data for most toxic form of cyanide (free cyanide) was used. IRIS, 2000; NLM, 2000, LDEQ RECAP 2000, USEPA Region IX, 1999 National Library of Medicine. 2000. Hazardous Substances Database. USEPA, 2000. Integrated Rask Information Systems (IRIS) Calculated from RIC following EPA Region IX Equation. Reference Exposure Levels. May and September, 1999. Inbalation reference concentration. Milligrams per kniegram per day. Volatile organic compounds. Milligrams per cubic meter Central nervous system. RECAP (LDEQ 2000). Oral reference dose. Gastromtestual No. available References: mg/kg/day тубш Š E E S CSS 5

Unon Pacifol LA001993 000 I/Tables/12-ToxifuRFD/bk 4/27/01/3 24 AM

Oral Cancer Slope Factors, Inhalation Cancer Slope Factors, Tumor Sites, and USEPA Cancer Classifications for Constituents of Concern, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana. Table 3.

	Oral CSF	Inhalation CSF		Tumor site	site	USEPA
Constituent	(kg-day/mg)	(kg-day/mg)		Oral	Inhalation	Classification
Acrylic Acid	NC	NC		NA	NA AN	
Aluminum	NC	SC		ΑN	NA A	
Саргојастат	NC	NC		NA	Ϋ́	
Chloromethane	0.013 a	0.0035	d	Ϋ́N	Ϋ́	ပ
Cyanide	SC	NC		NA	N A	
1,2-Dichloropropane	0.068 a	0.068	ঝ	liver	ΑΝ	<b>B</b> 2
Dicyclopentadiene	SC	SC		N.	NA AN	
Disodium Iminodiacetate	NA	NA		NA	NA	
Ethylene Glycol	SC	NC		NA AN	Y.	
n-Hexane	Š	NC		¥N	NA VA	
Neopentyl Glycol	NA	N.		NA	AN	
Pentane	ΝΑ	NA		AN	AZ	
Phenol	NG	SC		ΥΥ	Y.	
2,4-Toluenediamine	3.20 b	3.20	م	liver	Ϋ́	B2
Toluene Diisocyanate	0.039	0.0385	U	liver, pancreas	Ϋ́Z	B2

LDEQ RECAP, 2000 (a); USEPA Region IX, 1999 (b); California EPA (c); National Library of Medicine (HSDB), 2000. References:

Toluene Diisocyanate has not been formally listed as a carcinogen by the USEPA, but as a conservative measure

the California EPA carcinogenic evaluation was used.

Probable human carcinogen with sufficient evidence in animals and inadequate or no evidence in humans.

Possible human carcinogen.

Cancer slope factor. CSF

Kilograms-day per milligram.

Not available.

Not a carcinogen. kg-day/mg NA NC

mg/kg

Table 4 Calculation of RECAP Screening Standards for Soil, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana

	Soil_SSni	Soil_SSGW	Soil_sat
Constituent	(mg/kg)	(mg/kg)	(mg/kg)
Acrylic Acid	3.06%	139	381531
Aluminum	7495 38	66601 KENNE	NAP
Caprolactam	1932 57	<b>经</b> 数169.92 <b>%</b>	2444029.41
Chloromethane(Methyl Chloride)	5 80		1600
Cyanide (total)	149,914	400 <sup>(1)</sup>	232005.72
1,2-Dichloropropane	0.69	STATE OF THE STATE	1,200
Dicyclopentadiene	<b>2.3800年</b> 0.00点级64	1.11	NAP
Disodium Iminodiacetate	NA	NA	NA
Ethylene Glycol	5893.77	存在20215:3000000000000000000000000000000000000	14752.96
n-Hexane	學為20043年2月	158.67	215 23
Neopentyl głycol*	5893.77	EAST STATE OF THE	274405 11
n-Pentane	海道區的國際配	99.70	548.08
Phenol	2100		24536 19
2,4-Toluenediamine	0 08	<b>学课</b> (2010年)	1028.56
Toluene Diisocyanate	\$ 00 PM (0.74 )	2 68	251 87

NA Not available

NAP Not applicable.

RECAP Risk Evaluation/Corrective Action Program.

Soil\_sat Soil screening standard based on the concentration at which the pore spaces in the soil medium are saturated constituent of concern; from RECAP Table 2 when available.

Soil\_SSGW Soil screening standard based on the protection of groundwater meeting the definition of Groundwater

Classification I, from RECAP Table 1 when available.

Soil\_SSni Soil screening standard based on the protection of human health for non-industrial land use; from RECAP Ta

when available

milligrams per kilogram.

Soil level protective of groundwater for inorganic constituents based on GW1 because TCLP value not listed.
 Chloromethane's Soil\_SSGW In RECAP Table 1 is based on Quanitation limits, not the RECAP calculations.

Neopentyl glycol data was not available, therefore ethylene glycol was used as a surrogate.

Note: If the limiting Soil Screening Standard was below the analytical quantitation limits, the analytical quantitation

was used as the limiting soil RECAP standard (LDEQ 2000).

Limiting Screening Standards are shaded.

Table 5. Equations for RECAP Screening Standards for Soil and Sample Calculations for Soil, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

Soilssa for Noncarcinogenic Effects of Organic Constituents

$$Soil_{SSm}(mg/kg) = \frac{THQ \times BW_c \times AT_{nc} \times 365 daysl \ yr}{EF_m \times ED_c \left[ \left( \left( \frac{1}{RfD_o} \right) \times 10^6 \frac{kg}{mg} \times IRS_c \right) + \left( \left( \frac{1}{RfD_o} \right) \times IRA_c \times \left( \frac{1}{VF_m} \right) \right) + \left( \left( \frac{1}{RfD_o} \right) \times SA_c \times AF_c \times ABS \times 10^6 \frac{kg}{mg} \right) \right]}$$

Soil<sub>SSm</sub> for Carcinogenic Effects of Organic Constituents

$$Soil_{SSm}(mg/kg) = \frac{TR \times AT_c \times 365 daysl \ yr}{EF_m \times \left[ \left( CSF_o \times 10^{-6} \frac{kg}{mg} \times IRS_{odp} \right) + \left( CSF_i \times IRA_{odp} \times \left( \frac{1}{VF_m} \right) \right) + \left( CSF_o \times 10^{-6} \frac{kg}{mg} \times ABS \times IRD_{odp} \right) \right]}$$

Soil<sub>SSm</sub> for Noncarcinogenic Effects of Inorganic Constituents

$$Soil_{SSni}(mg / kg) = \frac{THQ \times BW_c \times AT_{nc} \times 365 days / yr}{EF_{ni} \times ED_c \times \left[ \left( \left( \frac{1}{RfD_o} \right) \times 10^{-6} \frac{kg}{mg} \times IRS_c \right) + \left( \left( \frac{1}{RfD_o} \right) \times SA_c \times AF_c \times ABS \times 10^{-6} \frac{kg}{mg} \right) \right]}$$

The following formulas are for both carcinogenic and noncarcinogenic constituents:

$$VF_{ni}(m^3/kg) = \frac{(Q/C)\times(3.14\times D_A\times T)^{1/2}\times10^{-4}(m^2/cm^2)}{(2\times\rho_b\times D_A)}$$

$$D_{A}(cm^{2}/s) = \frac{\left[\left(\theta_{a}^{10/3}D_{i}H' + \theta_{w}^{10/3}D_{w}\right)/n^{2}\right]}{\rho_{b}K_{d} + \theta_{w} + \theta_{a}H'}$$

$$C_{voil}(mg/kg) = \frac{GW_1 \times (\rho_b \times K_d + \theta_w + \theta_a \times H')}{\rho_b}$$

Table 5. Equations for RECAP Screening Standards for Soil and Sample Calculations for Soil, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

GW<sub>ss</sub> for Noncarcinogenic Effects of Non-volatile Constituents

$$GW_{SS}(mg/L) = \frac{THQ \times BW_a \times AT_{mn} \times 365 days/yr}{EF_m \times ED_m \times \left(\frac{1}{RfD_o} \times IRWa\right)}$$

GW<sub>SS</sub> for Noncarcinogenic Effects of Volatile Constituents

$$GW_{SS}(mg/L) = \frac{THQ \times BW_a \times AT_{nni} \times 365 days/yr}{EF_m \times ED_m \times \left(\left(\frac{1}{RfD_i} \times K_w \times IRA_a\right) + \left(\left(\frac{1}{RfD_o}\right) \times IRW_a\right)\right)}$$

$$GW_1 = GW_{ss} \times 10$$

GWss for Carcinogenic Effects of Non-volatile Constituents

$$GW_{SS}(mg/L) = \frac{TR \times AT_c \times 365 days/yr}{EF_{nl} \times (CSF_o \times IRW_{adj})}$$

GWss for Carcinogenic Effects of Volatile Constituents

$$GW_{ss}(mg/L) = \frac{TR \times AT_c \times 365 days/yr}{EF_{ni} \times \left[ \left( CSF_i \times K_w \times IRA_{adj} \right) + \left( CSF_o \times IRW_{adj} \right) \right]}$$

$$GW_1 = GW_{SS}$$

$$Soil_{SGB}(mg/kg) = C_{tot} \times 20$$

Table 5. Equations for RECAP Screening Standards for Soil and Sample Calculations for Soil, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

$$Soil_{sat}(mg/kg) = \frac{S}{\rho_b} ((K_d \times \rho_b) + \theta_w + (H' \times \theta_a))$$

Estimation of air and water diffusivities (D, and Dw)

chemical a = chemical in question chemical b = phenol (with published diffusivity value)

$$D_{i} = \frac{D_{ib}}{D_{ia}} = \sqrt{\frac{MW_{a}}{MW_{b}}}$$

$$D_{w} = \frac{D_{wb}}{D_{wa}} = \sqrt{\frac{MW_{a}}{MW_{b}}}$$

ABS	Dermal absorption factor (unitless)	chemical-specific
AF <sub>c</sub>	Child soil-to-skin adherence factor (mg/cm²)	0.3 mg/cm <sup>2</sup>
$AT_c$	Averaging time – carcinogens (yrs)	70 yr
AT <sub>nc</sub>	Averaging time – noncarcinogens (yrs)	6 yr
AT <sub>russ</sub>	Averaging time – noncarcinogens, non-industrial (yr)	30 yr
BW <sub>a</sub>	Adult body weight (kg)	70 kg
BW <sub>e</sub>	Average child body weight ages 1-6 (kg)	15 kg
$C_{soil}$	Soil concentration (mg/kg dry weight)	calculated
CSF,	Inhalation cancer slope factor (mg/kg-day)-1	chemical-specific
CSF <sub>o</sub>	Oral cancer slope factor (mg/kg-day)-1	chemical-specific
$D_A$	Apparent diffusivity (cm²/s)	calculated

Table 5. Equations for RECAP Screening Standards for Soil and Sample Calculations for Soil, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

Diffusivity in air (cm²/s)	chemical-specific
Diffusivity in water (cm <sup>2</sup> /s)	chemical-specific
Child exposure duration ages 1-6 (yr)	6 yr
non-industrial exposure duration (yr)	30 yr
non-industrial exposure frequency (days/yr)	350 days/yr
Fractional organic carbon in soil (g/g); $f_{oc}$ = percent organic matter/174 (ASTM 2974)	0.006 (0.6%)
The RECAP groundwater screening standard based on the protection of groundwater meeting the definition of Groundwater Classification 1.	calculated
RECAP standard for groundwater meeting the definition of Groundwater Classification 1.	calculated
Henry's Law Constant (atm-m³/mol)	chemical-specific
Dimensionless Henry's Law Constant; H'=H/RT=Hx41	chemical-specific
Adult inhalation rate (m³/day)	20 m³/day
Age-adjusted inhalation rate (m³-yr/kg-day)	11 m³-yr/kg-day
Child inhalation rate ages 1-6 (m³/day)	10 m³/day
Age-adjusted dermal contact rate (mg-yr/kg-day)	504 mg-yr/kg-day
Age-adjusted soil ingestion rate (mg-yr/kg-day)	114 mg-yr/kg-day
Child soil ingestion rate ages 1-6 (mg/day)	200 mg/day
Adult water ingestion rate (L/day)	2 L/day
	Diffusivity in water (cm²/s)  Child exposure duration ages 1-6 (yr)  non-industrial exposure duration (yr)  non-industrial exposure frequency (days/yr)  Fractional organic carbon in soil (g/g); foc = percent organic matter/174 (ASTM 2974)  The RECAP groundwater screening standard based on the protection of groundwater meeting the definition of Groundwater Classification 1.  RECAP standard for groundwater meeting the definition of Groundwater Classification 1.  Henry's Law Constant (atm-m³/mol)  Dimensionless Henry's Law Constant;H'=H/RT=Hx41  Adult inhalation rate (m³/day)  Age-adjusted inhalation rate (m³-yr/kg-day)  Child inhalation rate ages 1-6 (m³/day)  Age-adjusted dermal contact rate (mg-yr/kg-day)  Child soil ingestion rate ages 1-6 (mg/day)

Table 5. Equations for RECAP Screening Standards for Soil and Sample Calculations for Soil, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

$IRW_{adj}$	Age-adjusted water ingestion rate (L-yr/kg-day)	1.1 L-yr/kg-day
K <sub>d</sub>	Soil-water partition coefficient (cm <sup>3</sup> /g) = $K_{\infty} x f_{\infty}$	chemical-specific
K <sub>oc</sub>	Soil organic carbon partition coefficient (cm³/g)	chemical-specific
K <sub>w</sub>	Water-to-indoor air volatilization factor (L/m³)	0.5 L/m³
MW	Molecular weight (g/mole)	chemical-specific
n	Total soil porosity ( $L_{pore}/L_{soil}$ ); (1 - $\rho_b/\rho_s$ )	0.36
$\rho_{b}$	Dry soil bulk density (g/cm³)	1.7 .
$\rho_{\rm s}$	Soil particle density (g/cm³)	2.65
Q/C	Inverse of the mean concentration at the center of a 0.5-acre-square source (g/m²-s per kg/m³)	79.25
RfD,	Inhalation chronic reference dose (mg/kg-day)	chemical-specific
RfD <sub>o</sub>	Oral chronic reference dose (mg/kg-day)	chemical-specific
S	Solubility in water (mg/L-water)	chemical-specific
SA <sub>c</sub>	Child surface area (cm²/day)	2900 cm²/day
Soil <sub>sat</sub>	Soil saturation concentration (mg/kg)	calculated
Soil <sub>ssm</sub>	Non-industrial risk-based chemical concentration in soil (mg/kg)	calculated
Soil <sub>ssgw</sub>	Screening standard based on the protection of groundwater meeting the definition of Groundwater Clasification 1.	calculated
Т	Exposure interval (s) - Noncarcinogen Carcinogen	$1.9 \times 10^8$ $9.5 \times 10^8$

Table 5. Equations for RECAP Screening Standards for Soil and Sample Calculations for Soil, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

THQ	Target hazard quotient (unitless)	0.1
TR	Target excess individual lifetime cancer risk (unitless)	10-6
$\theta_{\mathtt{a}}$	Air-filled soil porosity ( $L_{aar}/L_{soil}$ ); (n- $\theta_{w}$ )	0.15
$\theta_{w}$	Water-filled soil porosity (L <sub>water</sub> /L <sub>soil</sub> )	0.21
$VF_{ni}$	Non-industrial soil-to-air volatilization factor (m³/kg)	chemical-specific

## **SAMPLE CALCULATION: Dicyclopentadiene**

Chemical a = dicyclopentadiene Chemical b = phenol

$$D_{i} = \frac{0.082cm^{2}/s}{D_{ia}} = \sqrt{\frac{132.21g/mole}{94.11g/mole}} = 0.0692cm^{2}/s$$

$$D_{wi} = \frac{0.0000091cm^2/s}{D_{wia}} = \sqrt{\frac{132.21g/mole}{94.11g/mole}} = 7.7x10^{-6}cm^2/s$$

$$D_{A} = \frac{\left[ \left( 0.15^{10/3} \times 0.07cm^{2} / s \times 0.0107atm - m^{3} / mol \times 41 \right) + \left( 0.21^{10/3} \times 7.7x10^{-6} cm^{2} / s \right) / 0.36^{2} \right]}{\left( 1.7g / cm^{3} \times 5.364cm^{3} / g \right) + 0.21 + \left( 0.15 \times 0.0107atm - m^{3} / mol \times 41 \right)}$$

$$= \frac{4.1x10^{-4}}{9.4} = 4.4x10^{-5} cm^{2} / s$$

$$VF_m = \frac{79.25 \times \left(3.14 \times 4.4 \times 10^{-5} \, cm^2 / s \times 1.9 \times 10^8 \, s\right)^{1/2} \times 10^{-4}}{2 \times 1.7 \times 4.4 \times 10^{-5} \, cm^2 / s}$$

Table 5. Equations for RECAP Screening Standards for Soil and Sample Calculations for Soil, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

$$=\frac{1.3}{0.00015}=8620m^3/kg$$

$$Soil_{SSai} = \frac{0.1 \times 15 \times 6 \times 365}{350 \times 6 \times \left[ \left( \left( \frac{1}{3x10^{-2}} \right) \times 10^{-6} \times 200 \right) + \left( \left( \frac{1}{5.7x10^{-5}} \right) \times 10 \times \left( \frac{1}{8620} \right) \right) + \left( \left( \frac{1}{3x10^{-2}} \right) \times 2900 \times 0.3 \times 0.1 \times 10^{-6} \right) \right]}$$

$$= \frac{3285}{2100(20.4)} = 0.08 \ mg / kg$$

$$GW_{SS} = \frac{0.1 \times 70 kg \times 30 y \times 365 days / yr}{350 d / y \times 30 y \times \left[ \left( \frac{1}{6x10^{-5}} \times 0.5 Lm^3 \times 20 m^3 / day \right) + \left( \frac{1}{3x10^{-2} mg / kg - d} \times 2L / d \right) \right]}$$
$$= \frac{76650}{1.75x10^9} = 4.4x10^{-5} mg / L$$

The analytical quantitation limit for Dicyclopentadiene in groundwater is 0.01 mg/L, therefore this value was used for GW<sub>1</sub> in the Csoil equation below.

$$Csoil = \frac{0.01mg/L(1.7g/cm^3 \times 5.364cm^3/g + 0.21 + 0.15 \times 0.011atm - m^3/mol \times 41)}{1.7g/cm^3} = 0.055mg/kg$$

$$Soil_{SSGW} = 0.055mg / kg \times 20 = 1.11mg / kg$$

Dicyclopentadiene is not soluble in water, therefore the Soil is considered not applicable.

Table 5. Equations for RECAP Screening Standards for Soil and Sample Calculations for Soil, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

## **SAMPLE CALCULATION:** Acrylic Acid

Chemical a = Acrylic Acid Chemical b = phenol

$$D_{i} = \frac{0.082cm^{2}/s}{D_{in}} = \sqrt{\frac{72.06g/mole}{94.11g/mole}} = 0.094cm^{2}/s$$

$$D_{wa} = \frac{0.0000091cm^2/s}{D_{wa}} = \sqrt{\frac{72.06g/mole}{94.11g/mole}} = 1.04x10^{-5}cm^2/s$$

$$D_{A} = \frac{\left[ \left( 0.15^{10/3} \times 0.094 cm^{2} / s \times 3.2 x 10^{-7} atm - m^{3} / mol \times 41 \right) + \left( 0.21^{10/3} \times 1.04 x 10^{-5} cm^{2} / s \right) / 0.36^{2} \right]}{\left( 1.7g / cm^{3} \times 5.364 cm^{3} / g \right) + 0.21 + \left( 0.15 \times 3.2 x 10^{-7} atm - m^{3} / mol \times 41 \right)}$$

$$=\frac{4.6x10^{-7}}{0.65}=7.1x10^{-7}cm^2/s$$

$$VF_{m} = \frac{79.25 \times \left(3.14 \times 7.1 \times 10^{-7} \text{ cm}^{2} / \text{s} \times 1.9 \times 10^{8} \text{s}\right)^{1/2} \times 10^{-4}}{2 \times 1.7 \times 7.1 \times 10^{-7} \text{ cm}^{2} / \text{s}}$$
$$= \frac{0.16}{2.4 \times 10^{-6}} = 67668 \text{m}^{3} / \text{kg}$$

$$Soil_{SSm} = \frac{0.1 \times 15 \times 6 \times 365}{350 \times 6 \times \left[ \left( \left( \frac{1}{0.5} \right) \times 10^{-6} \times 200 \right) + \left( \left( \frac{1}{0.00029} \right) \times 10 \times \left( \frac{1}{67668} \right) \right) + \left( \left( \frac{1}{0.5} \right) \times 2900 \times 0.3 \times 0.1 \times 10^{-6} \right) \right]}$$

$$= \frac{3285}{2100(0.51)} = 3.06mg / kg$$

Table 5. Equations for RECAP Screening Standards for Soil and Sample Calculations for Soil, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

$$GW_{SS} = \frac{0.1 \times 70 kg \times 30 y \times 365 d / y}{350 d / y \times 30 y \times \left(\frac{1}{0.5 mg / kg - d} \times 2L / d\right)}$$

$$= \frac{76650}{42000} = 1.8 mg / L$$

$$C_{soil} = \frac{10 \times 1.8 mg / L \left[ \left(1.7g / cm^3 \times 0.258 cm^3 / g\right) + 0.21 + \left(0.15 \times 3.2 x 10^{-7} \frac{atm - m^3}{mol} \times 41\right) \right]}{1.7g / cm^3} = 6.963 mg / kg$$

$$Soil_{SSGW} = 6.963mg/kg \times 20 = 139mg/kg$$

$$Soil_{sat} = \frac{1x10^6 \, mg \, / \, L}{1.7g \, / \, cm^3} \left[ \left( 0.26cm^3 \, / \, g \times 1.7g \, / \, cm^3 \right) + 0.21 + \left( 3.2x10^{-7} \, \frac{atm - m^3}{mol} \times 41 \times 0.15 \right) \right]$$
$$= 5.9x10^5 \left( 0.44 + 0.21 + 1.95x10^{-6} \right) = 3.8x10^5 \, mg \, / \, kg$$

## **SAMPLE CALCULATION: 2,4-Toluenediamine**

Chemical a = 2,4-toluenediamine Chemical b = phenol

$$D_{i} = \frac{0.082cm^{2}/s}{D_{ia}} = \sqrt{\frac{122.17g/mole}{94.11g/mole}} = 0.072cm^{2}/s$$

$$D_{wa} = \frac{0.0000091cm^2/s}{D_{waa}} = \sqrt{\frac{122.17g/mole}{94.11g/mole}} = 7.99x10^{-6}cm^2/s$$

Table 5. Equations for RECAP Screening Standards for Soil and Sample Calculations for Soil, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

$$D_A = \frac{\left[ \left( 0.15^{10/3} \times 0.072 cm^2 / s \times 1.2 x 10^{-9} atm - m^3 / mol \times 41 \right) + \left( 0.21^{10/3} \times 7.99 x 10^{-6} cm^2 / s \right) / 0.36^2 \right]}{\left( 1.7 g / cm^3 \times 0.013 cm^3 / g \right) + 0.21 + \left( 0.15 \times 1.2 x 10^{-9} atm - m^3 / mol \times 41 \right)}$$

$$= 1.47 x 10^{-6} cm^2 / s$$

$$VF_{m} = \frac{79.25 \times \left(3.14 \times 1.47 \times 10^{-6} \, cm^{2} / s \times 9.5 \times 10^{8} \, s\right)^{1/2} \times 10^{-4}}{2 \times 1.7 \times 1.47 \times 10^{-6} \, cm^{2} / s}$$
$$= \frac{0.52}{5 \times 10^{-6}} = 1.05 \times 10^{5} \, m^{3} / kg$$

$$Soil_{SSNI} = \frac{10^{-6} \times 70 \times 365}{350 \times \left[ \left( 3.2 \times 10^{-6} \times 114 \right) + \left( 3.2 \times 11 \times \left( \frac{1}{1.05 \times 10^{5}} \right) \right) + \left( 3.2 \times 10^{-6} \times 0.1 \times 504 \right) \right]}$$
$$= \frac{0.025}{0.3025} = 0.08 mg / kg$$

$$GW_{ss} = \frac{10^{-6} \times 70yrs \times 365days / yr}{350d / y \times (3.2 \times 1.1)}$$
$$= \frac{0.025}{1232} = 2.0x10^{-5} mg / L$$

The analytical quantitation limit for 2,4-Toluenediamine in groundwater is 0.02 mg/L, therefore this value was used for  $GW_1$  in the Csoil equation below.

$$C_{soil} = \frac{0.02mg / L \left( 1.7g / cm^3 \times 0.013cm^3 / g + 0.21 + 0.15 \times 1.2x 10^{-9} atm - m^3 / mol \times 41 \right)}{1.7g / cm^3} = 0.00274mg / kg$$

Table 5. Equations for RECAP Screening Standards for Soil and Sample Calculations for Soil, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

$$Soil_{SSGW} = 0.00274 mg / kg \times 20 = 0.055 mg / kg$$

$$Soil_{soil} = \frac{7.74 mg / L}{1.7g / cm^3} \Big[ \Big( 0.013 cm^3 / g \times 1.7g / cm^3 \Big) + 0.21 + \Big( 1.2x 10^{-9} atm - m^3 / mol \times 41 \times 0.15 \Big) \Big]$$

$$=4.55(0.0221+0.21+7.4x10^{-9})=1.06mg/kg$$

Calculation of RECAP Screening Standards for Groundwater, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana. Table 6.

	Carcinogenic	Noncarcinogenic		
			Minimum	Quantitation
Constituent	SS_WD	GW_SS	Value	Limit
	(mg/L)	(mg/L)	(mg/L)	(mg/L)
Acrylic Acid	SC	1.83	<b>操业等</b> 。第183章 <b>第2</b> 章	0 05
Aluminum	S	3.65	[1] [1] [1] [1] [1] [1] [1] [1] [1] [1]	0.5
Caprolactam	NC	1.83	[16] [16] [16] [16] [16] [16] [16] [16]	0.01
Chloromethane(Methyl Chloride)	0.002	0.005	######################################	0.002
Cyanide (total)	NC	0.073	高级的(0,079数例(2))	0.01
1.2-Dichloropropane	ΑΝ	ΝA	<b>特别</b> 数0:005.9条则	0.001
Dicyclopentadiene	SC	0.0004	0.00004	(25年,4年10/0/18年14年14年14年14年14年14年14年14年14年14年14年14年14年
Disodium Iminodiacetate	SC	NA	AN	NA
Ethylene Glycol	SC	.7.30	<b>(2000年)</b>	5.0
n-Hexane	SC	0.035	<b>编数数0033第段</b>	0.005
Neopentyl glycol +	SC	1.22	1.22	设有领的是CCOMMENSES
Pentane	ZC	0.035	<b>经数据</b> 项(035)	0.005
Phenoi	ZC	0.365	<b>数型流域0.365流域200</b>	0.01
2,4-Toluenediamine	0.00002	ΥN	0.00002	<b>经营业的00029000000000000000000000000000000000</b>
Toluene Diisocyanate	0.00029	0,000015	0.000015	(4)(2)(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)
•				

Milligrams per liter. mg/L ۲ ۲

Not available

Not a carcinogen. S

Risk Evaluation/Corrective Action Program RECAP

The minimum value for 1,2-Dichloropropane is the MCL value according to RECAP Worksheet 3.

Neopentyl glycol data were not available, therefore ethylene glycol was used as a surrogate.

If the GW\_SS was below the analytical quantitation limits, the analytical quantitation limit was used as the limiting groundwater RECAP standard (LDEQ 2000).

The shaded value was determined to be the limiting screening standard or the analytical quantitation limit.

Table 7. Equations for RECAP Screening Standards for Groundwater and Sample Calculations for Groundwater, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

GW<sub>ss</sub> for Noncarcinogenic Effects of Non-volatile Constituents

$$GW_{SS}(mg/L) = \frac{THQ \times BW_a \times AT_{nni} \times 365 days/yr}{EF_{ni} \times ED_{ni} \times \left(\frac{1}{RfD_a} \times IRWa\right)}$$

GWss for Noncarcinogenic Effects of Volatile Constituents

$$GW_{SS}(mg/L) = \frac{THQ \times BW_a \times AT_{mni} \times 365 days/yr}{EF_{ni} \times ED_{ni} \times \left(\left(\frac{1}{RfD_i} \times K_w \times IRA_a\right) + \left(\left(\frac{1}{RfD_a}\right) \times IRW_a\right)\right)}$$

$$GW_1 = GW_{SS} \times 10$$

GWss for Carcinogenic Effects of Volatile Constituents

$$GW_{SS}(mg/L) = \frac{TR \times AT_c \times 365 days / yr}{EF_{ni} \times \left[ \left( CSF_i \times K_w \times IRA_{adi} \right) + \left( CSF_o \times IRW_{adi} \right) \right]}$$

GW<sub>ss</sub> for Carcinogenic Effects of Non-volatile Constituents

$$GW_{SS}(mg/L) = \frac{TR \times AT_c \times 365 days/yr}{EF_m \times (CSF_o \times IRW_{adj})}$$

$$GW_1 = GW_{SS}$$

Table 7. Equations for RECAP Screening Standards for Groundwater and Sample Calculations for Groundwater, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

AT <sub>c</sub>	Averaging time – carcinogens(yrs)	70 уг
AT <sub>nni</sub>	Averaging time - noncarcinogens, non-industrial (yr)	30 yr
BW <sub>a</sub>	Adult body weight (kg)	70 kg
CSF,	Inhalation cancer slope factor (mg/kg-day)-1	chemical-specific
CSF <sub>o</sub>	Oral cancer slope factor (mg/kg-day)-1	chemical-specific
ED <sub>ni</sub>	non-industrial exposure duration (yr)	30 yr
EF <sub>ni</sub>	non-industrial exposure frequency (days/yr)	350 days/yr
GW <sub>ss</sub>	The RECAP groundwater screening standard based on the protection of groundwater meeting the definition of Groundwater Classification 1.	calculated
GW,	RECAP standard for groundwater meeting the definition of Groundwater Classification 1.	calculated
IRA <sub>a</sub>	Adult inhalation rate (m³/day)	20 m³/day
IRA <sub>adj</sub>	Age-adjusted inhalation rate (m³-yr/kg-day)	11 m³-yr/kg-day
IRA <sub>c</sub>	Child inhalation rate ages 1-6 (m³/day)	10 m³/day
IRW <sub>a</sub>	Adult water ingestion rate (L/day)	2 L/day
$IRW_{adj}$	Age-adjusted water ingestion rate (L-yr/kg-day)	1.1 L-yr/kg-day
K <sub>w</sub>	Water-to-indoor air volatilization factor (L/m³)	0.5 L/m <sup>3</sup>
RfD,	Inhalation chronic reference dose (mg/kg-day)	chemical-specific
RM <sub>o</sub>	Oral chronic reference dose (mg/kg-day)	chemical-specific

Table 7. Equations for RECAP Screening Standards for Groundwater and Sample Calculations for Groundwater, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

THQ

Target hazard quotient (unitless)

0.1

TR

Target excess individual lifetime cancer risk (unitless)

10-6

## **SAMPLE CALCULATION: Dicyclopentadiene**

$$GW_{SS} = \frac{0.1 \times 70 kg \times 30 y \times 365 days / yr}{350 d / y \times 30 y \times \left[ \left( \frac{1}{6x10^{-5}} \times 0.54 m^3 \times 20 m^3 / day \right) + \left( \frac{1}{3x10^{-2} mg / kg - d} \times 2L / d \right) \right]}$$
$$= \frac{76650}{1.75x10^9} = 4.4x10^{-5} mg / L$$

## **SAMPLE CALCULATION:** Acrylic Acid

$$GW_{SS} = \frac{0.1 \times 70 kg \times 30 y \times 365 d / y}{350 d / y \times 30 y \times \left(\frac{1}{0.5 mg / kg - d} \times 2L / d\right)}$$
$$= \frac{76650}{42000} = 1.8 mg / L$$

## **SAMPLE CALCULATION: 2,4-Toluenediamine**

$$GW_{ss} = \frac{10^{-6} \times 70 kg \times 365 days / yr}{350 d / y \times (3.2 \times 1.1)}$$
$$= \frac{0.025}{1232} = 2.0 \times 10^{-5} mg / L$$

Table 8 Calculation of RECAP Standards for Surface Water, Union Pacific Derailment Site, Union Pacific Railroad Company, Eurice, Louisiana

	Carcinogenic	Noncarcinogenic		
Constituent	SWNDW	SWNDW	Mınımum Value	Quantitation Limit
	(mg/L)	(mg/L)	(mg/L)	(mg/L)
Acrylic Acid	NC	321.10	132) Land	0.05
Aluminum	NC	636 47	10 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	0.5
Caprolactam	NC	228 76	2 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	0.01
Chloromethane(Methyl Chloride)	0 037	41 01	世界を大のいけるなど	0 002
Cyanide (total)	NC	12 84	<b>建筑</b> 区的线形态	001
1,2-Dichloropropane	0 002	0 17	<b>种原理 0.0051至201</b> 型	0 001
Dicyclopentadiene	NC	1 08	<b>沙村</b>	001
Disodium Iminodiacetate	NA	NA	NA NA	NA
Ethylene Glycol	NC	484	PARTY NAMED IN	50
n-Hexane	NC	43 21	<b>建筑</b> (公) (公) (公)	0 005
Neopentyl glycol*	NC	484 0	<b>美国国际</b> (4.4)(大学国际	20 0
n-Pentane	NC	43 93	Market Co.	0 005
Phenol	NC	166 93	<b>建設器166913水型</b>	001
2,4-Toluenediamine	0 0002	NA	0 0002	2. 名图频性Q.Q2基础分
Toluene Diisocyanate	0 00022	1 94	0 00022	44 (007)

BCF	Bioconcentration factor (	(L/kg) chemical specific

BWa Adult Body Weight (70 kg)

CSF<sub>0</sub> Oral cancer slope factor (mg/kg/day)<sup>-1</sup> -- chemical specific

IRF Fish/Shellfish ingestion rate (0 02 kg/day)
IRW<sub>NOW</sub> Incidental water ingestion rate (0 089 L/day)
log Kow Log of the octanol/water partition coefficient

MCL Maximum contaminant level

mg/L Milligrams per liter

RECAP Risk Evaluation/Corrective Action Program
RfD<sub>e</sub> Oral reference dose (mg/kg/day) -- chemical specific
SWNDW Risk-Based Concentration in surface water (mg/L)

NA Not available

THQ Target Hazard quotient (unitless) - 1
TR Target Risk Level (unitless) -- 10<sup>-6</sup>

The minimum value for 1,2-Dichloropropane is the MCL value according to RECAP Worksheet 3

Neopentyl glycol data were not available, therefore ethylene glycol was used as a surrogate

If the SWNDW was below the analytical quantitation limits, the analytical quantitation limit was used as the limiting groundwater RECAP standard (LDEQ 2000)

The shaded value was determined to be the limiting standard or the analytical quantitation limit

Equation taken from GW3NDW equation and is consistent with Human Health Numerical Criteria

Derivations for Toxic Substances, LDEQ 1994

noncarcinogenic

SWNDW =  $(THQ \times RID \times BW) / (IRW_{NDW} + (BCF \times IRF))$ 

carcinogenic

 $SWNDW = (TR^*BW)/(CSF^*(IRW_{NDW} + (BCF \times IRF)))$ 

Table 9. Equations for RECAP Standards for Surface Water and Sample Calculations for Surface Water, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

SW<sub>NDW</sub> for Noncarcinogenic Effects

$$SW_{NDW} = \frac{THQ \times RfD_o \times BW_a}{IRW_{NDW} + (BCF \times IRF)}$$

SW<sub>NDW</sub> for Carcinogenic Effects

$$SW_{NDW} = \frac{TR \times BW_a}{CSF_o \times (IRW_{NDW} + (BCF \times IRF))}$$

When chemical-specific data were not available, the following formulas were used.

$$LogBCF = 0.76 \log K_{ow} - 0.23$$

$$LogK_{OC} = 0.0784 + (0.7919 \times \log K_{OW})$$

BCF	Bioconcentration factor	chemical-specific
BW <sub>a</sub>	Adult body weight (kg)	70 kg
CSF <sub>o</sub>	Oral cancer slope factor	chemical-specific
IRF	Fish/Shellfish ingestion rate (kg/day)	0.02 kg/day
IRW <sub>NDW</sub>	Incidental water ingestion rate (L/day)	0.089 L/day
K <sub>oc</sub>	Organic carbon/water partition coefficient	chemical-specific
Kow	Octanol/water partition coefficient	chemical-specific
RfD <sub>o</sub>	Oral chronic reference dose (mg/kg-day)	chemical-specific
SW <sub>NDW</sub>	Risk-based concentration in surface water (mg/L)	calculated
THQ	Target hazard quotient (unitless)	1
TR	Target excess individual lifetime carner risk (unitless)	10⁴

LDEQ-EDMS Document 22570781, Page 37 of 40

<html><head><title>Object moved</title>
//cdms/poe/main/router.aspx?ref=https%3a%2f%2fedms.deq.louisiana.gov%2fapp%2fdoc%2fFnDocContent.aspx%3flib%3dDefaultIMS%253aLDEQ%253aFileNet%26doc%3d22570781%26page%3d37'>here</a>.
//body>
//html>

Calculation of Risk-Based Concentrations for Edible Fish (Based on EPA Region III RBC Table and Equations), Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana. Table 10

Detection Region III RBC Calculated -EoX

Limits

RBC

Carcinogen

Carcinogen

Constituent	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)
Acrylic Acid	NC	1825	是是是特殊的8000000000000000000000000000000000000	AN	100
Aluminum	NC	3650	是他们的一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个	1400	80
Caprolactam	Ş	1825	<b>特別的開始的</b> 多名類類的影響	089	1
Chloromethane	0.6551	314	元の教徒を対しては、	0.24	0.05
Cyanide	NC	73	可以在是一个人的人,	27	0.5
1,2-Dichloropropane	0.1252	4	(2) (2) (2) (2) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3	0.05	0.046
Dicyclopentadiene	Σ	110	AND THE PROPERTY OF THE PROPER	41	
Disodium Iminodiacetate	ΑN	ΨX	Ϋ́	Y.	1.2
Ethylene Glycol	NC	7300	SALES SALES OF THE SALES	2700	NA
n-Hexane	NC	219	<b>以他是一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个</b>	81	NA
Neopentyl glycol <sup>†</sup>	ŊC	7300	<b>建筑的1000000000000000000000000000000000000</b>	NA	4
n-Pentane *	SC	219		81	NA
Phenol	NC	2190	15 Cartina 15 Children 15 Chil	810	0.33
2,4-Toluenediamine	0.0027	ΑN	0.003	0.001	<b>医神经过水水水道水水水</b>
Toluene diisocyanate	0.2184	840	0.22	NA	<b>操印建新图 华地里的</b>
•					

Not available.

Not a carcinogen.

Milligrams per kilogram. mg/kg Risk-Based Concentrations.

RBC

Neopentyl glycol data was not available, therefore ethylene glycol was used as a surrogate.

Pentane data was not available, therefore hexane was used as a surrogate.

The formulas used to calculate the RBCs above are from EPA Region III. Note:

The fish ingestion rate was adjusted to meet the values in LDEQ RECAP.

प्रहार के जिल्ला The shaded value was determined to be the limiting screening standard or the analytical quantitation limit.

Table 11. Equations for Risk-Based Concentrations for Edible Fish and Sample Calculations for Risk-Based Concentrations for Edible Fish, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

**RBC** for Noncarcinogenic Effects

$$RBC = \frac{THQ \times RfD_o \times BW_o \times AT_n}{EF_r \times ED_{tot} \left(\frac{IRF}{1000 \ g / kg}\right)}$$

**RBC for Carcinogenic Effects** 

$$RBC = \frac{TR \times BW_o \times AT_c}{EF_r \times ED_{tot} \times \left(\frac{IRF}{1000 g / kg}\right) \times CSF_o}$$

AT <sub>c</sub>	Averaging time for carcinogens (days)	25550 days
AT <sub>n</sub>	Averaging time for noncarcinogens (days)	10950 days
$BW_a$	Adult body weight (kg)	70 kg
CSF <sub>o</sub>	Oral cancer slope factor (mg/kg-day) <sup>-1</sup>	chemical-specific
ED <sub>tot</sub>	Total exposure duration (years)	30 y
EF <sub>r</sub>	Exposure frequency (days/year)	350 d/y
IRF	Fisk ingestion rate (g/day)	20 g/day
RBC	Risk-based concentrations (mg/kg)	calculated
RfD <sub>o</sub>	Oral reference dose (mg/kg-day)	chemical-specific
TIIQ	Target hazard quotient (unitless)	1
TR	Target excess individual lifetime cancer risk (unitless)	10 <sup>-6</sup>

Table 11. Equations for Risk-Based Concentrations for Edible Fish and Sample Calculations for Risk-Based Concentrations for Edible Fish, Union Pacific Derailment Site, Union Pacific Railroad Company, Eunice, Louisiana.

### Sample Calculation: Dicyclopentadiene

$$RBC = \frac{1 \times 0.03 \frac{mg}{kg - d} \times 70 \, kg \times 10950 \, d}{350 \, d \, / \, yr \times 30 \, y \times \left(\frac{20 \, g \, / \, day}{1000 \, g \, / \, kg}\right)} = 110 \, mg \, / \, kg$$

#### **Sample Calculation: Acrylic Acid**

$$RBC = \frac{1 \times 0.5 \frac{mg}{kg - d} \times 70 \, kg \times 10950 \, d}{350 \, d \, / \, yr \times 30 \, y \times \left(\frac{20 \, g \, / \, day}{1000 \, g \, / \, kg}\right)} = 1825 \, mg \, / \, kg$$

## Sample Calculation: 2,4-Toluenediamine

$$RBC = \frac{10^{-6} \times 70 \, kg \times 25550 \, days}{350 \, d \, / \, yr \times 30 \, y \times \left(\frac{20 \, g \, / \, day}{1000 \, g \, / \, kg}\right) \times 3.2 \left(\frac{mg}{kg - day}\right)^{-1}} = 0.003 \, mg \, / \, kg$$